

The AquaPRO 4655 Water Conditioner

Start your day off with soft, conditioned water.



AquaPRO
Systems
4655

- 💧 *Limited Lifetime Warranty*
- 💧 *Stainless Steel Tank*
- 💧 *Electronic Control Valve*
- 💧 *Nickel Plated Brass Valve Body*
- 💧 *Superior High Capacity Resin*
- 💧 *Standard Bypass Valve Allows for Ease of Installation and Service*
- 💧 *Brine Tank with Safety Float*

Note: The 4655 Series Controls have been validated by the manufacturer through the Water Quality Association to meet industry Standard S-100-81.

Resin meets requirements of FDA regulation 21 CFR 173.25.



MADE IN U.S.A.

The New Wave

4655 Water Conditioner



SXT Timer
4655 Valve

The turbulator distribution system scrubs and cleans the resin bed for optimal efficiencies.

- Extra Cycle Button
- Easy Programming
- Bright red LED display
- Display Time of Day & Gallons of soft water remaining
- Service and Self Diagnostic Indicator
- Advanced programming options including up to six independently adjustable cycle times with time remaining displayed during regeneration

4655 BENEFITS



Softer, Fluffier Clothes



Save on Plumbing Fixtures & Repairs



Use Less Soaps and Detergents



Skin stays naturally smooth; hair silky clean

The AquaPRO Water 4655 Conditioner

SPECIFICATIONS

Model# Meter	Service Flow GPM	Valve Only Service Flow		Brine Tank (Lbs.)	Salt Per		Pipe Size	Tank Size	Min. Grains Capacity	Max. Grains Capacity	Shipping Weight
		Min.	Max.		Min.	Max.					
AP4655M-2	8	20	26	275	5	12	3/4" std.	8.5" x 36"	15,000	24,000	87 Lbs.
AP4655M-3	10	20	26	275	6	18.5	3/4" std.	8.5" x 48"	20,000	32,000	108 Lbs.
AP4655M-5	12	20	26	275	9	28	3/4" std.	10" x 48"	30,000	48,000	140 Lbs.
AP4655M-6	17	20	26	275	12	37	1" std.	12" x 48"	40,000	64,000	165 Lbs.

NOTES:

Units standard with 3/4" bypass. Request 1" connection when ordering if needed.

Specifications designed for optimal performance. Add approximately 6 inches to tank size to reach overall dimensions.

Manufacturer

Aqua Treatment Service Inc.
194 Hempt Rd.
Mechanicsburg, PA 17050

Dealer